



## Product Data Sheet Illustrating Film Thickness and Coverage

<b>LC</b>	<b>Solvent Borne Fluoroelastomer Coatings</b>	<b>Recommended Mils per App.</b>		<b>Coverage/Gallon Each Application</b>		<b>Coverage/1 mil/dft</b>	
		<b>Wet</b>	<b>Dry</b>	<b>ft<sup>2</sup></b>	<b>m<sup>2</sup></b>	<b>Gallon</b>	<b>Litre</b>
	<b>LC-8125</b>	8	1	200	19	200	53
<b>SS</b>	<b>Solvent Borne Fluoropolymer Coatings</b>	<b>Recommended Mils per App.</b>		<b>Coverage/Gallon Each Application</b>		<b>Coverage/@ 1 mil/dft</b>	
		<b>Wet</b>	<b>Dry</b>	<b>ft<sup>2</sup></b>	<b>m<sup>2</sup></b>	<b>Gallon</b>	<b>Litre</b>
	<b>SS-4208</b>	13	3	123	11	368	97
<b>WB</b>	<b>Water Borne Coatings</b>	<b>Recommended Mils per App.</b>		<b>Coverage/Gallon Each Application</b>		<b>Coverage/@ 1 mil/dft</b>	
		<b>Wet</b>	<b>Dry</b>	<b>ft<sup>2</sup></b>	<b>m<sup>2</sup></b>	<b>Gallon</b>	<b>Litre</b>
		<b>WB (Fluoroelastomer)</b>	2	1	810	75	810
<b>WBSS (Fluoropolymer)</b>	2	1	810	75	810	214	